

MSB

FOR THE BEST CUT. THE MSB.



The Schechtl MSB is the reinforced version of the SMT. It is even more solidly constructed than the SMT, which means higher cutting performance. The cutting material tray can be perfectly adapted to suit the material flow in your workshop – simply select the tilting table version which deposits sheets towards the front or towards the rear ex works.

BENEFITS

- ✓ **Precise** cutting quality – even with thicker sheet metal
- ✓ **High-quality, durable** shear blades
- ✓ **Optimum adjustment** to production processes
- ✓ **High degree of flexibility** in the production process through a wide range of variants
- ✓ **Automatic hold-down unit with slip-proof hard rubber insert** holds the sheet firmly in position

TECHNICAL DATA

Subject to change

MODEL	MSB		310	250	200	150	100
WORKING LENGTH		mm	3140	2540	2040	1540	1040
OUTPUT	Steel (400N/mm ²)	mm	2,00	2,50	3,00	3,50	4,00
	Stainless steel (600N/mm ²)	mm	1,25	1,50	2,00	2,25	2,50
	Aluminium (250N/mm ²)	mm	3,00	4,00	4,50	5,50	6,00
DIMENSIONS	Length	mm	3492	2892	2392	1892	1392
	Depth	mm	1965	1965	1965	1965	1965
	Overall height	mm	1450	1450	1450	1450	1450
WEIGHT		kg	1960	1640	1460	1290	1100

CONTROLS

TheMSBis available with the following controls.

- ✓ NC
- ✓ BVH
- ✓ NCH
- ✓ BV

SERIES EQUIPMENT

The following series equipment is possible depending on the version (working length/control):

- ✓ Steel shear blades
- ✓ Supporting plates with 10 mm scale
- ✓ Three-sided safety cage
- ✓ Foot switch
- ✓ Analogue position indicator
- ✓ Manual backgauge 0-750 mm + tilting table with front delivery
- ✓ Manual backgauge 0-750 mm + tilting table with rear delivery
- ✓ Programmable control unit with digital display
- ✓ Motorized backgauge 0-750 mm + tilting table with front delivery
- ✓ Motorized backgauge 0-750 mm + tilting table with rear delivery

ADD-ONS - OPTIMISE YOUR MSB

The following add-ons are possible depending on the version (working length/control):

- ✓ Shear blades for stainless steel
- ✓ Electronic position indicator
- ✓ Blank wagon (load capacity 300 kg)
- ✓ Blank wagon (load capacity 1,000 kg)
- ✓ Cutting gap illumination via LED
- ✓ Contact hub counter
- ✓ pneumatic hold-down unit
- ✓ Mitre angle limit
- ✓ Light barrier as a safety device

All details onMSB