TBS

MANOEUVRABLE AND MOBILE. THE TBS.



The Schechtl TBS is the smallest in our range of manual segment swivel bending machines, but a giant when it comes to flexibility on the job site. Its compact dimensions allow you to move the TBS around easily on the job site – between floors, on scaffolding and in small areas. Moreover, the TBS can be installed on a workbench or in a construction vehicle.

BENEFITS

- ✓ Bending **boxes, cassettes & co**. on the job site
- ✓ **Rational and productive** – all segments are adjusted without the use of tools
- ✓ **Without effort:** 1 man working alone can transport the TBS quite easily
- ✓ **Flexible:** Easy installation on any workbench or in a van
- ✓ **Safe storage** of the segments in a separate case

TECHNICAL DATA

Subject to change

MODEL	TBS		125	100
WORKING LENGTH		mm	1250	1000
OUTPUT	Steel (400N/mm²)	mm	0,63	0,63
	Stainless steel (600N/mr	mm	0,50	0,50
	Cooper (300N/mm²)	mm	0,80	0,80
	Aluminium (250N/mm²)	mm	1,00	1,00
	Zinc (150N/mm²)	mm	1,00	1,00
DIMENSIONS	Length	mm	1369	1235
	Depth	mm	698	698
	Overall height	mm	1156	1133
WEIGHT		kg	114	84
CLAMPING BEAMS	Opening height	mm	45	45

SERIES EQUIPMENT

The following series equipment is possible depending on the version (working length/control):

- ✓ Segments with quick clamping system
- ✓ Segment box

ADD-ONS - OPTIMISE YOUR TBS

The following add-ons are possible depending on the version (working length/control):

- ✓ Roller shear
- ✓ X-shaped support stand
- ✓ Stand bases

All details onTBS