# KSV

THE ALL-PURPOSE MACHINE. THE KSV.




**The Schechtl KSV is the reinforced version of the KS and also available with a working length of 2540 mm. The clamping beam consists of rolled profiles, the lower and bending beam of a steel construction. The comprehensive optional accessories and wide range of applications make the KSV the ultimate machine for the sheet metalworking trade.**

## BENEFITS

- ✓ **Virtually indestructible** – lasts for generations
- ✓ Realises **unusual profiles**
- ✓ **High working convenience** – back-friendly working height
- ✓ **Maintenance-free** bearings and guides
- ✓ **Versatile** through a comprehensive range of accessories

## TECHNICAL DATA

Subject to change

| MODEL | KSV | | 200 | 250 |
|---|---|---|---|---|
| WORKING LENGTH | | mm | 2040 | 2540 |
| OUTPUT | Steel (400N/mm²) | mm | 1,50 | 1,00 |
| | Stainless steel (600N/mr | mm | 0,90 | 0,60 |
| | Cooper (300N/mm²) | mm | 1,50 | 1,25 |
| | Aluminium (250N/mm²) | mm | 2,00 | 1,50 |
| | Zinc (150N/mm²) | mm | 3,00 | 2,50 |
| DIMENSIONS | Length | mm | 2675 | 3175 |
| | Depth | mm | 667 | 667 |
| | Overall height | mm | 1302 | 1302 |
| WEIGHT | | kg | 870 | 1090 |
| CLAMPING BEAMS | Opening height | mm | 80 | 80 |

# SERIES EQUIPMENT

The following series equipment is possible depending on the version (working length/control):

- ✓ Sharp rail 20° R 1 mm offset
- ✓ Insert rail 10 mm
- ✓ Insert rail 24 mm
- ✓ Foot pedal

# ADD-ONS - OPTIMISE YOUR KSV

The following add-ons are possible depending on the version (working length/control):

- ✓ Roller shear
- ✓ Manual back gauge 750 mm
- ✓ Beading apparatus
- ✓ Advice on rails

**All details onKSV**

Schechtl Maschinenbau GmbH
Viehhauser Str. 4
D-83533 Edling

(Zentrale) +49 8071 / 5995-0
(Sales) +49 8071 5995-111

WWW.SCHECHTL.DE