

TBS

MANOEUVRABLE AND MOBILE. THE TBS.



The Schechtl TBS is the smallest in our range of manual segment swivel bending machines, but a giant when it comes to flexibility on the job site. Its compact dimensions allow you to move the TBS around easily on the job site – between floors, on scaffolding and in small areas. Moreover, the TBS can be installed on a workbench or in a construction vehicle.

BENEFITS

- ✓ Bending **boxes, cassettes & co.** on the job site
- ✓ **Rational and productive** – all segments are adjusted without the use of tools
- ✓ **Without effort:** 1 man working alone can transport the TBS quite easily
- ✓ **Flexible:** Easy installation on any workbench or in a van
- ✓ **Safe storage** of the segments in a separate case

TECHNICAL DATA

Subject to change

| MODEL | TBS | | 125 | 100 |
|-----------------------|---|----|------|------|
| WORKING LENGTH | | mm | 1250 | 1000 |
| OUTPUT | Steel (400N/mm ²) | mm | 0,63 | 0,63 |
| | Stainless steel (600N/mm ²) | mm | 0,50 | 0,50 |
| | Cooper (300N/mm ²) | mm | 0,80 | 0,80 |
| | Aluminium (250N/mm ²) | mm | 1,00 | 1,00 |
| | Zinc (150N/mm ²) | mm | 1,00 | 1,00 |
| DIMENSIONS | Length | mm | 1369 | 1235 |
| | Depth | mm | 698 | 698 |
| | Overall height | mm | 1156 | 1133 |
| WEIGHT | | kg | 114 | 84 |
| CLAMPING BEAMS | Opening height | mm | 45 | 45 |

SERIES EQUIPMENT

The following series equipment is possible depending on the version (working length/control):

- ✓ Segments with quick clamping system
 - ✓ Segment box
-

ADD-ONS - OPTIMISE YOUR TBS

The following add-ons are possible depending on the version (working length/control):

- ✓ Roller shear
 - ✓ X-shaped support stand
 - ✓ Stand bases
-

All details onTBS